

REX™ HI-TEMP

REX™ Hi-Temp sets the standard in self-adhered underlayment. Install peace of mind with a Limited Lifetime warranty and 6-month UV protection. AQUA TRAK® technology assures maximum traction even in wet environments. Trust REX™ Hi-Temp for your most challenging roof coverings such as concrete, metal and tile.

PRODUCT SPECIFICATIONS

Roll Size	2 SQ
Length	66.67'
Width	3'
Rolls/Pallet	25
Pallets/Truck	28
Rolls/Truck	700
UV Exposure	6 Months
Warranty	Limited Lifetime



TECHNICAL SPECIFICATIONS

	Product Specifications	Test Method
Color	Gray	
Thickness	Pass	ASTM 1970
Adhesion to Plywood	Pass	ASTM 1970
Thermal Stability	Pass	ASTM 1970
Tear Resistance	Pass	ASTM 1970
Moisture Vapor Permeability	Pass	ASTM 1970
Capability to Seal Around Nail	Pass	ASTM 1970
Unrolling	Pass	ASTM 1970
Waterproof Integrity of Side Lap Seam	Pass	ASTM 1970

CODE APPROVALS

Florida Product Approval	FL46758
Code Listed	CCRR0533
Approved for High-Temp Installation	Yes

KEY FEATURES

- Top-tier protection for tile, metal, and concrete roofs
- Limited Lifetime Warranty
- 6-Month UV protection
- AQUA TRAK® = Safe, secure traction—even in the rain

This product is qualified for use as a component of a FORTIFIED-eligible roof system. Use of this product does not guarantee a FORTIFIED™ designation. To be eligible for a FORTIFIED designation, a complete roofing system (components and accessories) must meet the requirements detailed in the FORTIFIED Home™ Standard and be installed by a certified FORTIFIED Roofing Contractor. Products that are required to meet the standard include but may not be limited to: roof coverings, attic ventilation components, a qualified sealed roof deck system, roof underlayments, edge metal and appropriate fasteners for all mechanically fastened components. Documentation for all products and their installation is required. Additional requirements, eligibility criteria and restrictions apply. See the current FORTIFIED Home standard at <https://fortifiedhome.org/technical-documents/> for details.