

REX WRAP®

REX Wrap[®] is a durable, breathable, and easy-to-install solution for new builds or renovations. With up to 6 months of UV protection and a 10-Year Warranty, extendable to 25 years with our System Warranty, it delivers long-lasting performance across a variety of materials, due to its surfactant-resistant construction.

KEY FEAUTURES

- Ease of Installation: lightweight and easy to handle will save time and labor costs
- 6-month UV exposure
- 10-Year Warranty, extendable to 25 years for residential properties with our System Warranty

TYPICAL CHARACTERISTICS

	Test Method	Results
Composition		Woven Polypropelene
Weight		13.19 lbs per MSF
Water Vapor Transmission	ASTM E96 Method A	8
Water Penetration Resistance	ASTM D779	Pass
Tensile Strength	ASTM D5034	83 lbs MD
		52 lbs CD
Tear Resistance	ASTM D4533	47.1 lbs MD
		18.7 lbs CD
Thickness		5.5 mils
Smoke Develop Index	ASTM E84	Class A
Flame Spread Index	ASTM E84	Class A
UV Exposure		180 Days

ROLL SIZE	ROLLS PER UNIT
36"x100'	150
36"x150'	135
54"x100'	100
54"x150'	90
9'x100'	50
9'x150'	45
9'x195'	40
10'x100'	50
10'x150'	45
10'x195'	40

Enhance your build with our 25-Year System Warranty to guarantee long-term durability and performance. All components are designed to work seamlessly together for maximum results.









AlphaProTech PROTECH 25