

REX™ PREMIUM SEAM TAPE

Alpha ProTech has you covered with Premium Seam Tape

REX™ Premium Seam Tape is engineered for superior performance in the most demanding conditions. It delivers reliable adhesion and durability across a wide range of temperatures, making it ideal for both cold and warm weather applications.

Key Features:

- Formulated with a “quick-tack” adhesive to speed installation
- 3” wide versus standard 2” wide tapes (more surface area to cover seams)
- Excellent initial and long term adhesion
- Excellent chemical and thermal stability



PRODUCT SPECIFICATIONS

3"x165'	Per Roll
16 Rolls	Per Box
12 Boxes	Per Layer
8 Layers	Per Pallet
1,536 Rolls	Rolls per Pallet

When To Use:

- Horizontal and vertical overlaps between sheets of housewrap
- Around openings (windows, doors, vents) after the wrap is cut
- At the top termination where the wrap meets soffits or roof lines

TECHNICAL SPECIFICATIONS

Properties Tested	Results
Backing	Polyester PET
Adhesive Material	High Tack Adhesive
Thickness	3.22 mils
Adhesion (Peel)	60.0 oz./in.
Tensile Strength	20 lbs./in. width
Color	White
Roll Width	3 in.
Roll Length	165 Lineal Feet
Service Temperature	-22°F to 148°F
Application Temperature	-4°F to 105°F

REX™ Premium Seam Tape should not be stored at temperatures below 40°F (4°C), as lower temperatures may reduce adhesive tack and, in severe cases, prevent proper bonding to the substrate. To ensure optimal performance, the material should be stored in a controlled environment overnight and maintained at a minimum temperature of 60°F (15°C) prior to use.