

REX WRAP ROYAL

REX Wrap ROYAL is the perfect choice for demanding applications that require robust protection against severe weather conditions. Constructed from surfactant-resistant materials, it is ideal for use on wood, vinyl, metal, brick, stone, cement siding, or stucco.

KEY FEATURES

- Surfactant-Resistant
- Non-Woven Construction
- 15 Perms
- 6 Month UV Protection
- Approved for single-family residences and commercial properties up to 4 stories
- Limited Lifetime System Warranty



TYPICAL CHARACTERISTICS

	Test Method	Results
Basis Weight	ASTM D5261	105 GSM
Thickness	ASTM D3776	22 mils
Breaking Strength	ASTM D5034	75 lbs MD
		46 lbs CD
Tear Resistance (Trapezoid)	ASTM D4533	28/14
Air Barrier	ASTM E2178	0.0027
Hydrostatic Pressure	AATCC 127	Pass
Water Vapor Transmission Rate	ASTM E96 Procedure A	53 Perms
	ASTM E96 Procedure B	60 Perms
UV Exposure		6-months
International Code Council		ESR-5544
Flame Spread Index	ASTM E84	0 Class A
Smoke Develop Index	ASTM E84	10 Class A

ROLL SIZE

ROLLS PER UNIT

36"x100'	150
36"x150'	135
54"x100'	100
54"x150'	90
9"x100'	60
9"x150'	44
10"x100'	60
10"x150'	44

Enhance your build with our **Lifetime System Warranty** to guarantee long-term durability and performance. All components are designed to work seamlessly together for maximum results.

